

TOWN OF OSSIPEE Highway Dept. 55 Main Street, PO Box 67 Center Ossipee, NH 03814 Ph: (603) 539-8147

# **DRIVEWAY PERMIT APPLICATION**

		Map:	Lot:
tion shall be filed and approved tached to this application as a c	t, repair, or relocation of any driveway, end. Standards for driveways are contained in the checklist for conformance. These standard lirectly from Class V Town Roads.	in the Ossipee drive	eway regulations and are at-
Name of Owner:			
Address:			
Telephone:	Email:		
Name of Contractor (if applicab	ole):		
Contractor Telephone (if applica	able):		
Public road to Driveway:			
Estimated Length of driveway: _	Slope of land:	% Slope of Land	l Driveway:
Will this driveway provide acces	s to more than one living unit or use?	Yes: No:	
Are any states or federal approve	al permits required? Yes: ☐ No: ☐	If so, Please atta	ch.
Are you requesting a waiver? Ye	es: No: If so, state which section	ons:	
,	lations of the Town of Ossipee and under construction of this driveway within one y void.		1,
Signature o f Applicant:		I	Date:
ATTACH A SKETCH SHOW	VING (SEE ARTICLE V):		
• Location o f existing	g and/or proposed driveways(s) on lot from	ntage	
• Distance to other dr	iveways or roads within 200 ft. on both sic	les of the road	
• Width o f existing ar	nd/or proposed driveway(s)		
• Indication of sight of	distance in each direction		

NO APPLICATION WILL BE CONSIDERED UNLESS ACCOMPANIED BY APPROPRIATE SKETCH (See Article V)

Planned bridges, culverts, and or drainage ditches

## **DRIVEWAY PERMIT CHECKLIST**

## A. Driveway cuts on town roads.

4. When proposed driveway cuts on the same side of the road are within 50 of each other, a common access may be

2. No driveway cut within 150 ft. of the nearest edge of an intersecting road, measured between nearest edge.

3. A minimum of a 200 ft. of safe sight distance, both directions, through all seasons.

5. Driveway cuts shall intersect roadways at an angle of 60-90 degrees.

1. All driveway cuts shall be on Public Streets.

required.

of storm water.

6. The driveway cut shall slope down at a 5% grade for a minimum of 15' from edge of road.	
7. The driveway cut shall have a minimum width of 12 ft. at the intersection of the road. The cut may be flared out it approaches the road.	ıt a
8. If a culvert is required for proper drainage, the diameter shall be determined by Public Works Director or Highway foremen long enough to accommodate a 3:1 side slope, or to maintain the driveway width dimensions	
9. Culvert design shall conform to the most recent DOT specifications. The culverts shall be installed by the lar owner under the supervision and with the approval of the Public Works Director or designee.	ıd-
10. The drainage ditch shall be 6" below the outlet end of the culvert and drop at least 1/4" per foot to the nearest point of drainage relief.	st
11. Driveways shall not interrupt the natural or ditch line flow of drainage water. Where shallow ditch lines or natural drainage course drainage exist. Driveways may be swaled at a point beyond the shoulder to accommodate the flow	

## **DRIVEWAY PERMIT CHECKLIST**

## **B. ALL DRIVEWAYS**

1. All driveways shall be a minimum width o f 12 ft.

Date of Pre-Construction Approval:

- 2. No driveway shall have a slope of over 15%. Any driveway with a slope over 10% must be reviewed by the Public Works Director or their designee for safety issues.
- 3. Any driveway crossing a wetland or body of water shall have all permits required by the appropriate authority.

## PRE-CONSTRUCTION APPROVAL

Signature of Town Rep:
Town Rep Name and Title:
FINAL DRIVEWAY APPROVAL (POST-CONSTRUCTION)
Date of Final Approval:
Signature of Town Rep:
Town Rep Name and Title:
Property Owner Signature: