

TOWN OF OSSIPEE Highway Dept. 55 Main Street, PO Box 67 Center Ossipee, NH 03814 Ph: (603) 539-8147

DRIVEWAY PERMIT APPLICATION

Driveway Permit #:	Map: Lot:
Prior to construction, alteration, repair, or relocation of any driveway, er tion shall be filed and approved. Standards for driveways are contained tached to this application as a checklist for conformance. These standard ways in town that are accessed directly from Class V Town Roads.	in the Ossipee driveway regulations and are at-
Name of Owner:	
Address:	
Telephone: Email:	
Name of Contractor (if applicable):	
Contractor Telephone (if applicable):	
Public road to Driveway:	
Estimated Length of driveway: Slope of land:	% Slope of Land Driveway:
Will this driveway provide access to more than one living unit or use?	Yes: No:
Are any states or federal approval permits required? Yes: ☐ No: ☐	If so, Please attach.
Are you requesting a waiver? Yes: \(\subseteq \text{No:} \subseteq \text{If so, state which section} \)	ons:
I have read the Driveway Regulations of the Town of Ossipee and under tions, or failure to complete construction of this driveway within one yes hall render the permit null and void.	1,
Signature o f Applicant:	Date:
ATTACH A SKETCH SHOWING (SEE ARTICLE V):	
• Location of existing and/or proposed driveways(s) on lot from	ntage
• Distance to other driveways or roads within 200 ft. on both sid	des of the road
• Width o f existing and/or proposed driveway(s)	
 Indication of sight distance in each direction 	

NO APPLICATION WILL BE CONSIDERED UNLESS ACCOMPANIED BY APPROPRIATE SKETCH (See Article V)

Planned bridges, culverts, and or drainage ditches

DRIVEWAY PERMIT CHECKLIST

A. Driveway cuts on town roads.

No driveway cut within 150 ft. of the nearest edge of an intersecting road, measured between nearest edge.

A minimum of a 200 ft. of safe sight distance, both directions, through all seasons.

1. All driveway cuts shall be on Public Streets.

point of drainage relief.

of storm water.

4. When proposed driveway cuts on the same side of the road are within 50 of each other, a common access may be required.
5. Driveway cuts shall intersect roadways at an angle of 60-90 degrees.
6. The driveway cut shall slope down at a 5% grade for a minimum of 15' from edge of road.
7. The driveway cut shall have a minimum width of 12 ft. at the intersection of the road. The cut may be flared out as it approaches the road.
8. If a culvert is required for proper drainage, the diameter shall be determined by Public Works Director or

Highway foremen long enough to accommodate a 3:1 side slope, or to maintain the driveway width dimensions

owner under the supervision and with the approval of the Public Works Director or designee.

Culvert design shall conform to the most recent DOT specifications. The culverts shall be installed by the land-

10. The drainage ditch shall be 6" below the outlet end of the culvert and drop at least 1/4" per foot to the nearest

11. Driveways shall not interrupt the natural or ditch line flow of drainage water. Where shallow ditch lines or natural drainage course drainage exist. Driveways may be swaled at a point beyond the shoulder to accommodate the flow

DRIVEWAY PERMIT CHECKLIST

B. ALL DRIVEWAYS

1. All driveways shall be a minimum width o f 12 ft.

Date of Pre-Construction Approval:

- 2. No driveway shall have a slope of over 15%. Any driveway with a slope over 10% must be reviewed by the Public Works Director or their designee for safety issues.
- 3. Any driveway crossing a wetland or body of water shall have all permits required by the appropriate authority.

PRE-CONSTRUCTION APPROVAL

Signature of Town Rep:
Town Rep Name and Title:
FINAL DRIVEWAY APPROVAL (POST-CONSTRUCTION)
Date of Final Approval:
Signature of Town Rep:
Town Rep Name and Title: